

SYSTEM FOR THE CARE OF CONTACT LENSES

The invention relates to a system for the care of contact lenses according to the preamble of Claim 1.

In the case of such a system known from German Patent Document DE 196 24 095 C1, a receptacle is provided in which, for the care of contact lenses, a 3% H₂O₂-solution is provided for disinfecting contact lenses. The contact lens is immersed in this solution for treatment and storage. For the neutralization of the hydrous hydrogen peroxide solution, a platinum layer is situated on a molded body made of glass, which platinum layer may also be provided as an internal coating of the receptacle consisting of glass.

For the care of contact lenses, in addition to the disinfecting effect, the antimicrobial and antiviral effectiveness and a sufficient preservation are, however, also important, particularly when the contact lens is stored in the care solution for some time, which occurs, for example, in the case of adaptation (soft? - translator) contact lenses (DE 196 01 568 A1).

The oligodynamic effect, that is, the growth-inhibiting or killing effect of heavy metals, particularly of silver, on microorganisms is known. It was found, however, that, when

using silver (silvering) of the initially mentioned care system in the conventional manner, the durability of the platinum catalyst was impaired and the platinum layer catalysts had to be replaced after a short time.

It is therefore an object of the invention to provide a system of the initially mentioned type which, in addition to the oligodynamics of the care system, ensures a long durability of the platinum layer catalyst.

According to the invention, this object is achieved by the characterizing features of Claim 1.

The invention is based on the recognition that the durability of the platinum layer catalyst is not negatively impaired if the entire silver surface, which is effective in the hydrogen peroxide solution, does not exceed an upper limit. This upper limit is in the order of up to 25 mm²/ml of the H₂O₂ solution charged into the receptacle. The hydrous H₂O₂-solution is preferably a physiological solution with a physiological pH-value (approximately 6 to 8). Also in this solution, the desired antimicrobial long-term effectiveness is achieved by means of the silver metal layer which preferably is uniform and exists on a carrier. Within the disinfection phase (2 to 6 hours), after an inoculation with 10⁵ to 10⁶ KBE/ml of the test germs provided in the International Standard Draft ISO/CD 14729 (*pseudomonas aeruginosa*, *staphylococcus aureus*, *serratia marcescens*, *candida albicans*

and fusarium solani) and, in addition, aspergillus niger at the end of the disinfection phase, no growth was found, or a germ reduction by at least 5 powers of ten (5 log) was determined. After an inoculation with the poliovirus, a reduction to under the detection limit was obtained within 60 minutes. After the inoculation with the adenovirus a > 3 log reduction was obtained within 120 minutes; after 240 minutes, a >4.5 log reduction (virus below the detection limit) was obtained. After an inoculation with the HSV 1-virus, a > 3 log reduction (virus below detection limit) occurred within 30 minutes.

As a result, a single-stage system is created for the disinfection and preservation of contact lenses which is very effective during the disinfection and, during the storage of contact lenses, ensures (prevents? translator) their microbic contamination without the use of preservatives.

In a preferred manner, a silver surface is used of approximately 0.2 to 0.6, particularly 0.3 mm²/ml, of the hydrous H₂O₂ solution (3%) charged into the receptacle.

The silver layer with the indicated surface can be provided on a contact lens hold-down device by means of which the contact lens is immersed in the solution. This hold-down device can in a known manner be provided on the underside of a closing cover by which the receptacle is covered. By means of the hold-down device, it is prevented that, as a result of the

gases forming during the contact lens care and the neutralization of the care solution, the contact lens to be treated is driven to the surface of the care solution, but remains constantly immersed in the care solution.

The system for the care of contact lenses can be constructed as described in German Patent Document DE 197 57 356.8 A1. In this case, the receptacle, which receives the hydrous H_2O_2 -solution and the contact lens, can consist of glass and be coated on its interior side with a platinum layer catalyst. The platinum layer can be applied by sputtering. However, it is also possible to provide a molded body made of glass, which is provided with a platinum layer, in the receptacle (German Patent Document DE 196 24 095 C1). The silver layer will then preferably be situated on the contact lens hold-down device which is provided with bores so that the care solution will be present also over the hold-down surface which is immersed in the solution.

In another embodiment, the contact lens hold-down device can consist of glass, on one side of the hold-down device, particularly the underside, the platinum layer being arranged which is preferably applied by sputtering, and on the other side, particularly the top side of the hold-down device, the silver layer being arranged which can also be applied by sputtering. The receptacle can then also consist of plastic.

The invention will be explained by embodiments by means of the drawings.

Figure 1 is a view of a first embodiment; and

Figure 2 is a view of a second embodiment.

In the two embodiments of Figures 1 and 2, two cup-shaped receptacles 1, which are liquid-tight, are arranged in a case 4 in two receiving compartments 5 of the case. Each receptacle is used for receiving and for the care of a contact lens. On the exterior side of each receiving compartment 5, a thread is provided at the upper edge of the case 4, onto which thread a cover 3 can be screwed. However, it is also possible to provide a different holding device for the cover on the case, such as a clip-on device, holding clamps, or the like. As a result, a liquid-tight connection is established between the cover and the case. Inside the receiving compartments 5, the respective receptacles 1 are held at a distance from the cover underside and from the interior side of the respective receiving compartment 5. As a result, a space or spaces is/are created between the respective upper edge 6 of the receptacle and between the respective exterior side of the receptacle and the interior side of the respective receiving compartment 5, which space or spaces form(s) a passage for gases which are formed in the respective receptacles during the contact lens care. At the respective case 4, a bottom is provided on the underside. The case preferably consists of

plastic. The bottom may consist of plastic, particularly of metallized plastic, or of metal. As described in German Patent Document DE 197 57 356.8, the bottom may be fastened to the case 4 in a removable manner, for example, by means of a snap-on connection. As a result, it is ensured that gas, which is formed during the care of the contact lenses and during their storage in the receptacle, can escape through the created spaces.

In the illustrated embodiments, one hold-down device 6 respectively is provided. The hold-down device 6 has a hold-down surface which is immersed in the charged care solution. The care solution consists of a 3% H_2O_2 -solution. As a result of the effect of this care solution, the immersed contact lenses are disinfected. In order to avoid hydrogen peroxide residue on the contact lenses after the care, as a result of the effect of a platinum layer 2, the hydrogen peroxide is decomposed into oxygen and hydrogen (neutralized).

In the embodiment of Figure 1, the platinum layer 2 is situated on the interior side of the receptacle 1 consisting of glass. On the hold-down device 6, a silver layer 7 is situated which, similar to the platinum layer 2, can be applied by sputtering to the top side of the hold-down device 6. The hold-down device 6 has bores, so that the care solution can penetrate through the hold-down surface and it is ensured that the contact lens immersed by the hold-down surface will be situated below the surface of the charged care

solution. The applied silver layer 7 is also always situated within the filling volume of the charged care solution. As a result, an oligodynamic effect of the solution is achieved during the disinfection phase, in which the hydrogen peroxide has an effect, as well as after the neutralization of the hydrogen peroxide solution.

In the embodiment of Figure 2, the platinum layer 2, which acts as a neutralization catalyst, is situated on the underside of the hold-down device 6. The silver layer 7 is situated on the top side of the hold-down device 6. In this embodiment of Figure 2, the hold-down device 6 is made of glass. The silver layer 7 is preferably produced by sputtering. The surface of the silver layer 7, which is in contact with the H_2O_2 -solution, amounts to maximally $30 \text{ mm}^2/\text{ml}$, relative to the filling volume of the H_2O_2 -solution. In the embodiment of Figure 2, the receptacle 1 may consist of glass or of another material, such as plastic.

Instead of the hold-down device 6, small baskets can be used which are each provided on the underside of the cover 3 and carry the silver layer 7. The hold-down device and the small storage basket ensure that the contact lens is always immersed in the care solution. Gases forming during the neutralization and care cannot drive the lens to the surface of the care solution. As a result, a constant care of the immersed contact lens is achieved.

In the following Tables 1 and 2, the oligodynamic effect of different embodiments of the care system is illustrated in the case of various test organisms. In this case, neutralized hydrogen peroxide solutions (isotonic, pH 6.5, < 5 ppm residual content of hydrogen peroxide) are inoculated with approximately 10^6 microorganisms per ml of solution. Based on the tables, also in the case of relatively small silver layer surfaces (between 0.15 and 2.0 mm²/ml), the oligodynamic effect occurs which is achieved over a fairly long time period, which effect is important particularly for the care of adaptation (soft?) contact lenses.

Translation of Tables

Testorganismus test organism

Ag-Oberfläche Ag surface

Ausgangs-Inokulum initial inoculum

Logarithmische Reduktion der Testmikroorganismen =
logarithmic reduction of test microorganisms

Ausgangs-KBE initial KBE

Stunde hour

Stunden hours

Tage days

Durchschnittswert einer Doppelbestimmung =
average value of a repeat determination

KBE: Anzahl der koloniebildenden Einheit =

KBE: Number of the colony-forming unit

n.g.: kein Wachstum n.g.: no growth

List of Reference Number

- 1 Receptacle
- 2 platinum layer
- 3 cover
- 4 case
- 5 receiving compartments
- 6 hold-down device
- 7 silver layer
- 8 bottom

